









AUTOMATIC PACKAGING OR BUNDLING

P.O.BOX:1371, THESSALONIKI IND. AREA - 570 22, GREECE - ÔEL.: +30 2310 685 969, FAX: +30 2310 685 971

SEMI-AUTOMATIC



OPTIONAL SHRINK TUNNEL





e-mail: sales@kavafakis.gr info@kavafakis.gr

> www.kavafakis.eu www.kavafakis.gr

Model Types

Automatic Wrapping & Shrinking Automatic Wrappers Semi Automatic with Shrinking

STA SA ST

TECHNICAL FEATURES

- Shrinking for open or close type packaging.
- Maximum diameter of the plastic roll = Φ300
- Material used = polyethylene 30 60 micron.
- Metallic skeleton
- Electrical unwinding of 2 roll films simultaneously.
- Pneumatic pusher for feeding products.
- Automatic cutting and joining of the upper and lower film.
- Welding station with adjustable stopping mechanism
- Electronic automation board 380V, 50Hz with an auxiliary circuit 24Volt.
- High quality electric accessories.
- Maximum production speed = 15 bundles/minute.
- Accident protection
- Can be upgraded to adjust an automatic label feeding
- Metallic conveyor belt into the shrinking tunnel.
- Shrinking tunnel with double insulation.
- Lateral ironing of ready package.













SPECIAL FEATURES examples:

Model ST-80 & STA-80

- Maximum package dimensions: Length=500mm. Width =600mm. Height =335mm
- Maximum width of roll of plastic film =750mm
- Maximum power = 16.6 kW.

Model ST-110 & STA-110

- Maximum package dimensions: Length=500mm, Width =900mm, Height =390mm
- Maximum width of roll of plastic film = 1050mm
- Maximum power = 20.7 kW

4 widths available

> 60 80

sales@kavafakis.gr e-mail: info@kavafakis.gr

www.kavafakis.eu